



Star Couplings

| Coupling Size | Torque (NM) | KW at 100 RPM | Finish Bore | | Ø A | Ø B | L | Weight Approx |
|---------------|-------------|---------------|-------------|-----|------|-----|-----|---------------|
| | | | Min | Max | | | | |
| SJC 75 | 9.8 | 0.10 | 10 | 20 | 44.5 | 39 | 55 | 0.5 |
| SJC 90 | 15.5 | 0.15 | 15 | 28 | 54 | 49 | 56 | 0.7 |
| SJC 95 | 21.1 | 0.22 | 15 | 28 | 54 | 49 | 63 | 0.8 |
| SJC 99 | 35.1 | 0.37 | 20 | 35 | 65 | 57 | 72 | .1.5 |
| SJC 100 | 46.4 | 0.49 | 20 | 35 | 65 | 57 | 88 | 1.5 |
| SJC 110 | 89 | 0.93 | 20 | 45 | 85 | 76 | 108 | 3.0 |
| SJC 150 | 141 | 1.49 | 30 | 48 | 96 | 80 | 115 | 3.7 |
| SJC 190 | 190 | 2.01 | 36 | 60 | 115 | 102 | 133 | 6.8 |
| SJC 225 | 265 | 2.75 | 40 | 65 | 127 | 111 | 153 | 9.1 |
| SJC 226 | 327 | 3.45 | 25 | 70 | 137 | 119 | 178 | 12.0 |
| SJC 276 | 532 | 5.60 | 25 | 75 | 157 | 127 | 200 | 18.0 |
| SJC 280 | 782 | 8.20 | 30 | 85 | 192 | 140 | 200 | 24.0 |
| SJC 295 | 1279 | 13.40 | 40 | 100 | 237 | 162 | 238 | 44.0 |

